ELETRONIC GIFTS

MAC2014 MACARON POWERBANK

TRENDSPOTTING ELECTRONIC GIFT - PERFECT BALANCE OF SIZE & POWER



- Tiny, external battery pack roughly the size of a macaron round cake, yet capable
 of providing even the largest phones more than 2 hours of additional talk time.
- Extra talk time of 12+ hours for iPhone 6 Plus
- Ready to power your phone whenever you need to stay connected.
- Never miss an important phone call or urgent email.
- Macaron PowerBank is the perfect balance of power and size.

TECHNICAL DATA

Input	5V/1A
Output	5V/1A
Battery	2400mAh
Protection	Over-charge & discharge protection and short-circuit protection
Operating conditions	0 to +45 °C, 10 – 85 % RH
Storage conditions	-10 to +60 °C, 10 – 85 % RH
Dimensions	53x30mm
Weight	65g

SECW 2014 MINI WHEEL POWERBANK



TECHNICAL DATA

LUIINIUAL DAIA		
Input	5V/1A	
Output	5V/1A	
Battery	2400mAh	
Protection	Over-charge & discharge protection and short-circuit protection	
Operating conditions	0 to +45 °C, 10 – 85 % RH	
Storage conditions	-10 to +60 °C, 10 – 85 % RH	
Dimensions	53x30mm	
Weight	65g	

HIGH CAPACITY BUNNY POWER STICK









- Tiny, external battery pack roughly
- Yet can fully charge > 1 time of iPhone 6 Plus.
- Ready to power your phone
- Cute Bunny PowerBank is the perfect balance of power and size.
- Battery Capacity : 5000 mAh

TECHNICAL DATA

Input	5V 1.8A Max (Smart Charge)
Output	5V 1.8A Max
Battery	5000 mAh /3.7V
Charge Time	Approx. 3 hours (under max 1.8A)
Protection	Over-charge & discharge protection and shotrt-circuit protection
Operating conditions	0 to +45 °C, 10 – 85 % RH
Storage conditions	-10 to +60 °C, 10 – 85 % RH
Dimensions	35x109mm
Weight	80g

MINI SECURITY GADGET ST2014



- 1 On/Off table lamp
- 2 On/Off alarm siren (double press) 3 Release button for USB plug
 - 4 Battery status display 5 USB plug
- 6 Slot for spare SD card

TECHNICAL DATA

COMMICAL DATA	
Battery	LiPO 230 mAh/3.7V
Solar Panel	5V/20mA
USB charging	200 mA
LED	0.5W, 700-900 LUX
Sirwn	100-120 dB(100mm)
Operating conditions	0 to +45 °C, 10 – 85 % RH
Storage conditions	-10 to +60 °C, 10 – 85 % RH
Dimensions	90x35x20mm
Weight	32g



ELETRONIC GIFTS

SUPER MINI POWER BANK (CORDLESS)



SUPER MINI PORTABLE & EMERGENCY CHARGING DEVICES

- One of the world's smallest phone charger
- A compact and small enough to carry with you at all times, measuring up at a mere 2.3cm x 3.4cm x 4.2cm.
- With its strap hole, it is easy to attach it to keys or slipped into a pocket or fits in that tiny

Instant & cordless charging. No cable hassle

More options on PB123 Sleeves:



RECHARGEABLE BATTERY

USB

RECHARGE ANYWHERE



TECHNICAL DATA (USB AA Rechargeable Battery)

tion	AA
	NIMH
у	1200mAh
l Voltage	1.2V
nended Charge	250mAh
g Time	5-7 hours
intemal impedance	<35 milliohoms@1kHz
	17g
	y I Voltage nended Charge g Time internal impedance

APPLICATIONS





REVOLUTIONARY RECHARGEABLE BATTERY

- Recharge anywhere, anytime Red Charging Charged No cable or charger required
- Built-in mini charging circuit inside for portable convenience

Environmental-friendly USB rechargeable battery



RECHARGEABLE BATTERY

• Small & Light Weight enough to carry with you at all times.

Easy to attach to keys or slipped into a pocket.

TECHNICAL DATA Input voltage/Current Battery (Primary)

Battery (Secondary)

Operating conditions

Storage conditions

Weight

USB 18650 RECHARGE ANYWHERE

• Rechargeable battery gives you around 2-3 hours of extra talk time, up to a 2 days of

22.8x34x45mm

35g (Super light weight,small & compact)



TECHNICAL DATA (USB 18650 Rechargeable Battery)

Input	5V/1A
Output	3.7V/1A
Battery	1400 mAh
Protection	Over-charge & discharge protection and shotrt-circuit protection
Operating conditions	0 to +45 °C, 10 – 85 % RH
Storage conditions	-10 to +60 °C, 10 – 85 % RH
Dimensions	18.6x65.2mm
Weight	38g

APPLICATION





Smart Team Holdings Limited

C511

SMART TEAM



www.smartteam-ltd.com.hk

2016-2017 Product Hightlights

Flat A01, 5/F., Great Wall Fty Bldg., 11 Cheung Shun Street, Lai Chi Kok, Kowloon, Hong Kong Tel: (852) 3428 6032 Fax: (852) 3428 6033 eMail: sales@smartteam-ltd.com.hk

尺寸: 210X297mm 2016-09-22

AUTOMOBILE ELECTRONICS

PCC18-A & PCC18-B

3-IN-I CAR JUMP STARTER



PCC18-B (White LED)

MUTLI-FUNCTION

capacity battery













A very practical auto accessory for more than just emergencies

Packing a lot of power in a small package, newer portable car starters can really save the day in an emergency. They're great for traveling on vacation because they also have charging ports or USB ports to keep your favorite portable electronic devices fully charged. Your kids will thank you!

It's so compact that you will be able to store it virtually anywhere in your car out of the way

1. Jump Start Your Car

Easy-to-use vehicle jump starter can be setup in a matter of seconds to jump start your battery and can be used multiple times up to 50 before needing a charge.

2. Mobile Charging

2 USB ports (5 V/DC 2.1A x 2) to support charging most of your portable electronic devices which can also be a lifesaver in an emergency when you need your mobile phone the most. Can charge 2 devices at the same time.

PCC2014 CYLINDRICAL CAR JUMP STARTER

Jump Start Your Vehicle Without All the Hassle - Comes with a jumper cable cord that easily plugs into the battery booster.



MULTI-FUNCTIONS



















Perfect companion at all the time while you are driving on camping expeditions, travel, riding, boating, and during cold winter months.

1. Jump Start Your Car

Easy-to-use vehicle jump starter can be setup in a matter of seconds to jump start your battery and can be used multiple times up to 20 before needing a charge.

2. Mobile Charging

4 USB ports (Total 5A) to support charging most of your portable electronic devices which can also be a lifesaver in an emergency when you need your mobile phone the most. Can charge 4 devices at the same time.

3. LED Flashlight

Low and strong modes of white light for illumination.

3. Laptop Charging

Power bank includes 12V/16V/19V DC output with a switch for easy voltage selection 3 voltage/current modes to choose \longrightarrow DC 12V/3A, 16V/3A, 19V/2.5A

4. Built-in LED Flashlight with Warning Signal Built-in ultra-bright LED flashlight

PCC18-A

White Light : "dim" → "medium" → strong Warning lights : red & white flash alternatively.

White Light : "dim" \rightarrow "medium" \rightarrow strong.

5. LED indicators

5 LED status lights monitory battery level

Blue LED of power indication - 20%-40%-60%-80%-100% Green LED of charging indication

ERR indication of operating temperature if too high

6. Safety

Provides safety protection against overcharging, over-discharge, over-current, and short

Safety measures certified by CE, FCC, and RoHS

TECHNICAL DATA

Battery	18,000 67Wh (6000mAh x 3S, 3.7V)
Input	15V Max 1A, Max Charging Voltage Limit: 18V
Output (2 USBs)	5V /DC 2.1A + 2.1A
Output (DC)	3 Modes: 12V/3A, 16V/3A, 19V/2.5A
LED	PCC18-A: 10 Whites & 8 reds LEDs, PCC18-B: 3W LED
Self-discharge Current	<=100uA (Standby Mode)
Sleep Current of MCU	<2uA
Charging Time	Appro x 4-5h
Operating conditions	0 to +45 °C, 10 – 85 % RH
Storage conditions	-10 to +60 °C, 10 – 85 % RH
Dimensions	89.5x230x35mm
Weight	701g

4. Warning Lights & SOS nodes of red & white light flash : 1) alternatively and 2) together

5. Hand Warmer

Fast warmer start up in 2 seconds

6. Strong Magnet

Adhere the product to flat top surface in hand-free mode

4 LED status lights monitory battery level Blue LED of power indication - 25%-50%-75%-100%

8. Size & Shape (Patented)

Just the size of a soft drink can for placement and easy access from your car

Adopted with advanced intelligent circuitry and multiple security protection design: Over-charge, over-discharge, short-circuit, over-heat protection Safety measures certified by CE, FCC, and RoHS

TECHNICAL DATA

Battery	12000 mAh (4000mAh x 3S/3.7V)
Input	12-24V/2A Max
Charging Time	2.5-3H (Under car start condition)
Output	5V/5A Max (4 USB ports)
Discharge Time	1.5H (Under max output current in an independent mode)
Operating conditions	0 to +45 °C, 10 – 85 % RH
Storage conditions	-10 to +60 °C, 10 – 85 % RH
Dimensions	66x157mm
Weight	637.5g



AUTOMOBILE ELECTRONICS

PCC 17331

CAR CHARGER WITH MOVABLE TORCH HEAD



This 2-in-1 device lets you charge and store power for a handy torch!

- Charge your phone and other devices via the USB port
- Store power to take on the go for the mini torch
- Plug into the cigarette charging port to recharge

Car Charger

Always getting caught with low battery? Don't fret, this nifty device can charge your phone – just plug it into a cigarette port for quick and easy charging!

Light up inside your car

Lost something in the dark? Just pull the torch head up and down in any angle upto 150

PCC2818B

CAR CHARGER WITH IONIZER & GLASS BREAKER



Simply "charges" the air and keeps it chean, fresh and odor free



1. HIGH SPEED CHARGING

Dual USB output with high speed charging at 2.1A@

2. POWER UP IONIZER & CHARGING YOUR ELECTRONIC GADGETS -NO BATTERY

Easy to use, plug into cigarette socket and use directly

3. NEGATIVE ION PURIFIER

Anions > 3 millions per cm3

4. NO CHEMICAL COMPOSITION

No odor, no toxic & safe, Can be used 24 hours a day

5. PURIFY YOUR AIR INSIDE YOUR CAR

Eliminate dust, pollen, odors and even airborne bacteria and virus around you.









Flashlight on the go

In addition to regular charging, this device can store power to power up the torch with you when you're out and about. Once the ON/OFF button is pressed on, the high-power 1W LED flashlight can be used anytime, anywhere.

Highlights:

1. USB port

Torch

- 2. Power indicator
- 4. 300-degree head rotation

TECHNICAL DATA

Input voltage to product	12 – 24 V/DC	
Battery	Lithium polymer battery 3.7V 250mAh	
Input voltage/current to battery	5 V/DC, 500mA	
(When the product is connected to the cigarette lighter socket, it will charge the battery at 5V/500mA and at the same time it can charge external device connected via its USB 2.0 port)		
Output voltage/current	5 V/DC, 1500mA Max (Smart Charge)	
Torch (Movable head)	1W LED (~ 4 hours of use)	
Operating conditions	0 to +45 °C, 10 – 85 % RH	
Storage conditions	-10 to +60 °C, 10 – 85 % RH	
Dimensions (Diameter x Height)	43.9x102.7 mm	
Weight	40g (light weight & compact)	

5. WINDOW GLASS BREAKER

When confronted with an emergency, use your charger to break your car window and



TECHNICAL DATA

Input voltage	12-24V/DC
Output (2 USBs)	5V/DC, 2.1A x 2
Anions	> 3 millions / cm3
Ozone	< 0.02 ppm
Operating conditions	0 to +45 °C, 10 – 85 % RH
Storage conditions	-10 to +60 °C, 10 – 85 % RH
Dimensions	74.81 x 41.23 mm
Weight	70g



Ai408

HEALTH & PERSONAL CARE

PORTABLE & PERSONAL AIR PURIFIER

Simply "charges" the air and keeps it chean, fresh and odor free





This personal & portable ionizer let you create your own "clean" chamber of living environment in public area, while it is small and compact to carry with you.

- 1. POWER UP IONIZER NO BATTERY Easy to use, plug into portable power bank and use directly.
- 2. NEGATIVE ION PURIFIER

3. NO CHEMICAL COMPOSITION

4. PURIFY YOUR AIR INSIDE YOUR CAR

Eliminate dust, pollen, odors and even airborne bacteria and virus around you. No more second-hand smoking.







TECHNICAL DATA

Operating Voltage	5 V/DC
Operating Current	100mA
Output Voltage	-DC6.0KV±1.0KV(relative humidity:70% temperature:18 °C
Anions	>20,000,000/cm3
Ozone	<0.05 ppm
Operating conditions	0 to +45 °C, 10 – 85 % RH
Storage conditions	-10 to +60 °C, 10 – 85 % RH
Dimensions (LxWxH)	43.3x33x67mm
Weight	83g

OUTDOOR PRODUCT

MCL88

COOLING FAN

3 modes, from weak to strong respectively.

volume & with channel selection.

LED STATUS INDICATORS

FM RADIO & MOSQUITO REPELLER (ELECTRONIC)

LED 1/2/3 is indicator for power strength. LED 4 is status indicator for mosquito repellant function. LED 5 is status indicator for FM radio.

CAMPLING LANTERN / COOLING FAN

1W LED Flashlight

DISCOVER THE EYE-CATCHING **CAMPING FLASHLIGHT LANTERN COMBO**



1W LED FLASHLIGHT 3 modes, from weak to strong respectively CAMPING LIGHT (24 LEDS)

FC CE ROHS Compliant







POWER INDICATORS

There are 3 LEDs to indicate the strength of remaining power in battery with inc power strength with the increased number of LEDs on. 1 LED on is low power, 2 LEDs on is medium power and 3 LEDs on is high power.

While using the product, power indicator will light up and will switch off after open 10

WEATHER & DROP RESISTANT RECHARGEABLE HANG-UP HANDLE









ALL FUNCTIONS CAN WORK AT THE SAME TIME

TECHNICAL DATA

5,400 mAh (1800mAh x 3S/3.7V)
5V/DC,Max 1.8A(Micro USB,smart charge)
Approx. 3.5 hours (1.8A)
1W LED (Strong - 16H, Medium 27H, Low - 50H)
24 LEDs (Strong - 3.5H,Medium 5.5H,Low - 8H)
Strong -3.5H,Medium - 9.5H,Low -20H
103.5H (Standalone Use)
540H (Standalone Use)
IPX5
1M/3FT
0 to +45 °C, 10 – 85 % RH
-10 to +60 °C, 10 – 85 % RH
183x103mm
510g





尺寸: 210X297mm 2016-09-22